

PRODUCT SPECIFICATION

	Grade Availability by GSM								Units	Tolerance	
	54	58	60	64	70	80	90	100			
GSM	54	58	60	64	70	80	90	100	g/m ²	±2.5%	
Bulk	1.40	1.35	1.35	1.32	1.30	1.25	1.25	1.25	cc/gm	min.	
Cobb	25								g/m ²	max.	
Brightness	94								% ISO	±1	
Opacity	91	92	92	92	93	94	94	94	%	±1	
Wax Pick	14A								no.	min.	
Breaking Length	MD	5500	5500	5500	5500	5500	5200	5200	5200	mtr	±200
	CD	2700	2700	2700	2700	2700	2500	2500	2500		
Tear Factor	MD	50								-	min.
	CD	60									
Bendsten Smoothness	TOP	120-160								ml/min	max.
	BOTTOM	140-180									

PACKING INFORMATION

REELS

Width: 210-2200 mm

Core Inner Dia: 76 mm/ 3"

SHEETS

Min. Size: 390 x 510 mm

Max. Size: 900 x 1350 mm

PALLETS

Min. Height: 1100 mm

Max. Height: 1300 mm

DECKLE

4400 mm

For more information, please contact your Khanna Paper Mills representative or visit our website at www.khannapaper.com

This information is subject to modification without notification.



Khanna Paper Mills Limited

